VA703m

17" VALUE SERIES LCD MONITOR
WITH MULTIMEDIA

High quality, high performance.

The 17" ViewSonic VA703m is the all-in-one price performance solution for all needs. No matter if your use is for entertainment or for intensive graphics, whether in the home or in the office, the VA703m fits the bill perfectly. Its 8ms response time delivers crisp images and fluid full-motion video for games, movies and scrolling-text. Matched with 600:1 contrast levels and 280cd/m² brightness, the VA703m displays brilliant, vivid, true-to-life colours. Invisible built-in speakers deliver true multimedia performance. The slim styling and silver-black bezel add to the monitors appeal. Prepare to be impressed by the performance, quality and style of the VA703m.

It's not just a great value LCD. It's a ViewSonic.

IMPRESSIVE PERFORMANCE WITHOUT THE HIGH PRICE TAG

> ClearMotiv™ 8ms video response time
Ultra-fast 8ms video response delivers broadcast-quality full motion video.

> Multimedia enhanced
Save workspace and enjoy rich sound with built-in invisibel stereo speakers.

> High brightness and contrast
280cd/m² brightness (typ.) and 600:1 contrast ratio (typ.) for clear, detailed images.

> Full 17"– Viewable screen with 1280 x 1024 resolution
Displays a full, flat 17" viewable area with crisp details and fully saturated colours.

> Stylish slim-bezel design
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.

> OnView® controls for superior screen adjustability
Screen adjustments are precisely made via an easy-to-use on-screen menu.

> OSD/Power lock secures your settings
Prevents changes to monitor settings and maintains an optimised image.

> Integrated power supply

> VESA® 100mm wall mount interface and Kensington® security port

> PC and Mac® compatible

> TCO'03 and EnergyStar™ qualified

MORE THAN 2000 AWARDS

VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
the choice of professionals

ViewSonic
the choice of professionals

VA703m

17" VALUE SERIES LCD MONITOR WITH MULTIMEDIA

LCD	Type	17" TN colour TFT active matrix XGA LCD
	Display Area	33.8cm horizontal x 27.0cm vertical; 43.2cm diagonal
	Pixel Pitch	0.264mm
	Optimum Resolution	1280 x 1024@60Hz
	Pixel Clock	135MHz
	Contrast Ratio	600:1 (typ.)
	Viewing Angle	150° horizontal, 135° vertical (at 10:1) 170° horizontal, 155° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit + 2-bit FRC)
	Light Source	Long life, 50000 hrs. (min.)
	Brightness	280cd/m^2 (typ.)
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Frequency	F_h: 30 – 82kHz, F_v: 50 – 85Hz
	Synchronisation	H/V separate (TTL)
COMPATIBILITY	PC	VGA up to 1280 x 1024 non-interlaced (@60Hz preferred)
	Mac®[1]	Power Mac™ up to 1280 x 1024 non-interlaced (@60Hz preferred)
CONNECTOR	Analogue	15-pin mini D-Sub (attached cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	2 x 1 watt integrated invisible stereo speakers
POWER	Voltage	AC 100 – 240V, 50/60Hz (auto switch), internal power supply
	Consumption	36 watt (max.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	Power, menu [1], up, down, select [2]
	OSD	Auto image adjust, contrast, brightness, audio adjust (volume, mute), ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language [English, Finnish, French, German, Italian, Japanese, Spanish, Simplified Chinese, Traditional Chinese], resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITONS	Temperature	0°C – 40°C
	Humidity	10% – 90% (non-condensation)
DIMENSIONS	(W x H x D mm)	379 x 400 x 210 (with stand)
WEIGHT	Net	3.6kg (with stand)
	Gross	4.8kg
REGULATIONS		TCO'03, CE, CB, TÜV/GS, TÜV/Ergo, ISO13406-2 (pixel failure class II), UL/cUL, FCC-B, NOM, GOST-R, ENERGY, BSMI, CCC, (PSB), (C-TICK), Green Mark, WEEE, RoHS
POWER MANAGEMENT		Meets TCO'03 and ENERGY standards
SECURITY		Kensington® security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE		LCD Monitor, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ISO 9001 FM 40187 ISO 14001 EMS 40968

I Sistemi di Gestione Qualità e Gestione Ambiente di ViewSonic Corporation sono stati certificati ISO 9001 e ISO 14001 dalla British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom
Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)9 5406 4070
ViewSonic Italy	Tel: +39 02 73 95 50 22
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

[1] May require optional Mac adapter.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VA703m-07/06-UK